











Profil Profile	Referenz Reference	Flächenpressung Surface pressure (N/mm ²) *	Temperatur Temperature (°C) *	Geschwindigkeit Speed (m/s) *	Werkstoff Material	Abmess. Dim. (mm)			Seite Page
							mm	inch	
	10WR	25°C: ≤ 40 ≥ 60°C: ≤ 25	-40 +110	0,8	POM	0 ... 300	●		206 - 207
	10WR/I	25°C: ≤ 40 ≥ 60°C: ≤ 25	-40 +110	0,8	POM	0 ... 300		●	206 - 207
	10I/DWR	25°C: ≤ 40 ≥ 60°C: ≤ 25	-40 +110	0,8	POM	10 ... 300	●		208 - 209
	10FIL	25°C: ≤ 40 ≥ 60°C: ≤ 25	-40 +110	0,8	POM	10 ... 500	●	●	210 - 211
	10FIT	25°C: ≤ 40 ≥ 60°C: ≤ 25	-40 +110	0,8	POM	10 ... 500	●	●	210 - 211

5a für Stangen - for rods

	10WR	25°C: ≤ 40 ≥ 60°C: ≤ 25	-40 +110	0,8	POM	0 ... 300	●		212 - 213
	10WR/I	25°C: ≤ 40 ≥ 60°C: ≤ 25	-40 +110	0,8	POM	0 ... 300		●	212 - 213
	10E/DWR	25°C: ≤ 40 ≥ 60°C: ≤ 25	-40 +110	0,8	POM	10 ... 300	●		214 - 215
	10WP	25°C: ≤ 40 ≥ 60°C: ≤ 25	-40 +110	0,8	POM	0 ... 85	●		216 - 217
	10FET	25°C: ≤ 40 ≥ 60°C: ≤ 25	-40 +110	0,8	POM	10 ... 500	●	●	218 - 219

5b für Kolben - for pistons

